



# C 70 SLIDING DOOR - PVC

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 1.3 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: **24 mm.**

Maximum acoustic insulation: **Rw = 38 dB.**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

**Class 4**

Water tightness (UNE-EN 12208:2000):

**Class 7A**

Wind resistance (UNE-EN 12210:2000):

**Class C5**

Reference test window 1.23 x 1.48 m. 2 sashes.

SECTIONS	Frame 70 mm Three-rail 125 mm Sash 46 mm	OPENING POSIBILITIES	Sliding door 2, 3, 4 and 6 sashes. Optionally three-rail
CLASIFICACION	Profile thickness Class A $\geq 2.8$ mm Weather Severe weather Impact Class II	FINISHES	Optionally bicoloured White Coloured wrapping Wood-imitation wrapping
MAXIMUM DIMENSIONS	Width (L) = 1,700 mm Height (H) = 2,200 mm		
MAXIMUM WEIGHT/SASH	140 Kg.		

Please consult maximum dimensions according to types.

