



CLASSIC RAILING

POSIBILIDADES Y ALTURA MÁXIMA

POSIBILIDADES

Glazed railing
Glazed railing with clear top edge
Bar railing
Bar railing with clear top edge

HANDRAIL OPTIONS

Square - 60 mm width
Circular - 60 mm diameter
Elíptico - 80 mm external perimeter

CATEGORIES ACHIEVED AT TEST CENTRE

Tests according to UNE 85237:1991, UNE 85.238:1991 and UNE 85240:1990, requirements established in CTE (DB SU-1 y DB SE-AE) y requirements established in Eurocode 1 according to EN 1991-1-1:2003 /AC:2010

CLASIFICACION ACCORDING TO UNE 85240:1990: **Class A-EXCELLENT**

Reference test on railing made of extruded aluminium and glazing, fixed to edge slab with total dimensions 1100mm (H) x 1500mm (L) referred to floor level.

Reference test on railing made of extruded aluminium and glazing, fixed over the slab with total dimensions 1100mm (H) x 1500mm (L) referred to floor level.

MINIMUM HEIGHT 900 mm

MAXIMUM
DIMENSIONS
BETWEEN
PILASTERS 1,000 mm

EXTRUSION ALLOY 6063 T-5

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

