

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 1.0 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **46 mm.**

Maximum accoustic insulation: **Rw = 48 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1200

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 1.20 x 1.16 m. 2 sashes.

SECTIONS	Frame 60 mm Sash 68 mm
PROFILE THICKNESS	Window 1.6 mm Balcony 1.6 mm
MAXIMUM DIMENSIONS	Width (L) = 1,500 mm Height (H) = 2,600 mm
MAXIMUM WEIGHT/SASH	160 Kg.

Please consult maximum dimensions according to types.

FINISHES	<p>Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns</p> <p>Wood effect powder coating According to Qualideco standard</p> <p>Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured</p>
HERRAJE	<p>Optionally concealed hinges</p> <p>Optionally security hardware</p>

EXTRUSION ALLOY	6063 T-5
POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass : 24 mm
GASKETS	EPDM triple gasket
FOAMS	Perimeter polyolefin foam in glazing rebate zone
OPENING POSIBILITIES	
INWARDS	Side hung, turn&tilt, bi-fold, tilt and parallel-tilt
OUTWARDS	Side hung, top hung and pivoting on horizontal or vertical axis.

