

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 0.8 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **58 mm.**

Maximum accoustic insulation: **Rw = 46 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1500

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 1.23 x 1.48 m. 2 sashes.

SECTIONS	Frame 70 mm Sash 75 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Window 1.5 mm Balcony 1.7 mm	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass: 35 mm
MAXIMUM DIMENSIONS	Width (L) = 1,600 mm Height (H) = 2,800 mm	GASKETS	EPDM triple gasket
MAXIMUM WEIGHT/SASH	150 Kg.	FOAMS	Perimeter polyolefin foam in glazing rebate zone
FINISHES	Colour powder coating (RAL, mottled, rough...) According Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured	OPENING POSIBILITIES	INWARDS Side hung, turn&tilt, bi-fold, tilt and parallel-tilt OUTWARDS Side hung and top hung

Please consult maximum dimensions according to types.

