

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 1.3 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: **35 mm.**

Maximum accoustic insulation: **Rw = 45 dB.**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

**Class 4**

Water tightness (UNE-EN 12208:2000):

**Class E1500**

Wind resistance (UNE-EN 12210:2000):

**Class C5**

Reference test window 1.30 x 1.55 m. 1 Sash.

SECTIONS	Frame 70 mm Sash 69 mm	EXTRUSION ALLOY
PROFILE THICKNESS	Window 1,5 mm	6063 T-5
MAXIMUM DIMENSIONS	Width (L) = 1,600 mm Height (H) = 2,800 mm	POLYAMIDE STRIP LENGTH
MAXIMUM WEIGHT/SASH	150 Kg.	Polyamide 6.6 reinforced with 25% fiberglass : Frame 35 mm Sash 16 y 20 mm
FINISHES	Colour powder coating (RAL, mottled, rough...) According Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured	GASKETS
		EPDM triple gasket
		FOAMS
		Perimeter polyolefin foam in glazing rebate zone
		OPENING POSIBILITIES
		INWARDS Side hung, turn&tilt, tilt and parallel-tilt.

Please consult maximum dimensions according to types.

