



MILLENNIUM 2000 DOOR

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 2.3 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **30 mm.**

Maximum accoustic insulation: **Rw = 38 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Resistance to soft body impact
(UNE-EN 13049:2003)

Class 5 (máx)

Reference test door 1.80 x 2.20 m. 2 sashes. Laminated glazing 3+3

SECTIONS	Frame 45 mm Sash 45 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Door 2.0 mm	GASKETS	EPDM double gasket
MAXIMUM DIMENSIONS	Width (L) = 1,450 mm Height (H) = 3,000 mm Side hung door Width (L) = 1 Sash 2,000 mm 2 sashes 3.000 mm Height (H) = 3,000 mm Automatic sliding door Width (L) = 1,100 mm Height (H) = 3,000 mm Swinging door	OPENING POSIBILITIES	INWARDS Side hung 1 and 2 sashes OUTWARDS Side hung 1 and 2 sashes SWINGING DOOR 1 or 2 sashes AUTOM. Inwards and outwards 1 sash side hung and 1 and 2 sashes sliding door
MAXIMUM WEIGHT/SASH	190 Kg. 120 Kg. (automatic version)		
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25		

Please consult maximum dimensions according to types.

